

Jiri Hanzl - Ladislav Bartuska - Elena Rozhanskaya - Petr Prusa *

APPLICATION OF FLOYD'S ALGORITHM ON TRANSPORT NETWORK OF SOUTH BOHEMIAN REGION

The introductory part of the paper deals with the theory of searching for optimal routes in transport networks, including a description of each type of optimization tasks. The aim of the article is demonstration of Floyd algorithm application to find the minimal paths from each node to another in network graph - in our case the network represents traffic model of road network in the region of South Bohemia.

Keywords: Distance Matrix, Traffic Network, Transport Model, Floyd Algorithm, Optimal Route, Minimal Path.

1. Introduction

Finding the optimal routes in networks (transport network, telecommunication network, etc.) is the most common task of Graph Theory used in everyday life. These tasks are solved within the models of real transport networks. An example of a schematic model of the transport network may be a common non-oriented, connected and edge-rated graph. We are searching for optimal routes at this graph (model) because we need, for example, to minimize the costs necessary for realization of journeys. Minimizing the costs (such as the fuel consumption) can be understood as a task of finding the shortest (minimal) path between two specified nodes in the graph.

But it is not always about the minimizing of costs. Tasks of the reliability and capacity belong to the issue of route optimization in networks as well. These examples belong to the tasks of important routes within the graph [1]:

- Task of the shortest (minimal) path;
 - from one specific node of graph (origin) to another;
 - a) searching for minimal path from origin to final destination;
 - searching for minimal path from origin to all other nodes of graph;
 - from each node to one another;
- task of the most reliable path;
- · path with a maximum capacity;
- finding the maximum path in the graph (adjusted general algorithm).

In the following part a task of optimal route is generally formulated and a practical demonstration of the application of a simplified Floyd's algorithm on the transport network of I and II class roads in South Bohemian region is conducted for searching optimal routes in the network. Specifically, it is the application of the algorithm in the task of finding the minimal path from each of the network vertex to another [2].

2. Formulation of the problem of optimal route in network

Let us have a transport network as graph $G = (X, U, \varphi(h))$ wherein each edge $h \in U$ is rated with number $\varphi(h)$, called the edge length. Then the task of the optimal route in a network of n nodes (vertexes) is to find the optimum route, namely [3]:

- from one node ν_i (i.e. start or origin vertex) to other node ν_j
 (i.e. the destination or final vertex) in the network;
- from the initial node v_i to each of the other nodes $v_j \in X$ in the network; $v_i \in v_k$
- from every node v_i ∈ X to each another final node v_j in the network; v_i ≠ v_j
- between all pairs (v_i, v_j), or between ordered pairs [v_i, v_j]; v_i ≠ v_j;
 i, j = I,..., n.

When choosing the best option, some optimality criterion always enters into the solution of the problem. For example, in dealing with the problem of possible routes between two nodes we can assess distance (length) of possible routes, the consumption

^{* &}lt;sup>1</sup>Jiri Hanzl, ¹Ladislav Bartuska, ²Elena Rozhanskaya, ³Petr Prusa

¹The Institute of Technology and Business in Ceske Budejovice, Faculty of Technology, Czech Republic

²Plekhanov Russian University of Economics, Department of Foreign Economic Activity, Russia

³University of Pardubice, Jan Perner Transport Faculty, Department of Transport Management, Marketing and Logistics, Czech Republic E-mail: hanzl@mail.vstecb.cz

of time needed for the relocation, the mutual availability of the nodes and the costs associated with relocation.

However, we always come to the two extreme tasks, namely [3 and 4]:

- to minimum => task to find the minimal path;
- to maximum => task to find the maximal path.

The most common practical example is the criterion of optimizing the costs associated with relocation, and because our demand is to minimize the distance after which the relocation occurs. In application on the transport network of South Bohemian Region we will discuss the task of finding minimal paths between all nodes in the graph $G = (X, U, \varphi(h))$ [4].

2.1 Model of transport network in South Bohemian Region

As already mentioned in the introductory part of the article, simplified transport network is composed of I and II class roads (Fig. 1). Based on the real map and real conditions the traffic model was created (non-oriented graph $G=(X,U,\varphi(h))$) showing simply the same transport network with the valuation of individual edges with the distance [km], but for simplicity intersections in rural areas are neglected - intersections of network are merely nodes = cities with a population over 5,000. This simplified model of the network is then shown in Fig. 2.




Fig. 1 The road network of South Bohemian Region with the nodes towns and cities with population over 5,000 (source: http://www.mapy.cz) [5]




Fig. 2 A simplified model of the transport network in the South Bohemian Region with values of edges (km) (source: Authors)

2.2 Minimal paths from one node to another

The bulk of the tasks requires the calculation of distances between any two network nodes, thus the task is to find the minimal path between all pairs of nodes (v_i, v_j) , more precisely between ordered pairs $[v_i, v_j]$ in graph $G = (X, U, \varphi(h))$, where $v_i \neq v_j$ and i, j = 1, ..., n. In the selected transport network the output of the algorithm will be a square matrix of minimum distances D of type $n \times n$, where n = number of nodes (towns and cities with more than 5,000 inhabitants) in the graph, in the case of the South Bohemian Region n = 16. The whole graph is thus shown as a square 16×16 matrix where the row and column headings constitute individual nodes (cities) of the graph (Fig. 3) [6].

2.3 Floyd Algorithm

To demonstrate the practical use of the algorithm in practice, Floyd algorithm determining the minimal path from each node to another one was chosen. This algorithm is suitable for all transport networks having the number of edges approaching the complete graph. The algorithm is applicable to oriented and non-oriented graphs. In the case of simplified transport network of South Bohemia region it will be a non-oriented graph $G = (X, U, \varphi(h))$.

1) First, we prepare the initial square matrix of direct distance $C_{k=0} = (c_{ij})_{i,j=1}^n$ of $n \times n$ type so that:

$$c_{ij} = \varphi(h), if \exists h \in U: p(h) = (v_i, v_j), i \neq j$$

$$c_{ij} = 0 \text{ for } i = j$$

$$c_{ij} = \infty, if \text{ exists } h \in U: p(h) = (v_i, v_j), i \neq j$$

$$(1)$$

for all i, j = 1, ..., n. [3]

C ₀	TA	PI	ST	Volyně	Vimperk	Volary	CK	T. Sviny	Třeboň	JH	Soběslav	Týn n. Vlt.	Vodňany	PT	Netolice	CB
TA	0	45	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	20	32	1E+12	1E+12	1E+12	1E+12
PI	45	0	22	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	28	22	1E+12	1E+12	1E+12
ST	1E+12	22	0	13	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	26	1E+12	1E+12	1E+12
Volyně	1E+12	1E+12	13	0	18	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	26	25	1E+12	1E+12
Vimperk	1E+12	1E+12	1E+12	18	0	27	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	23	1E+12	1E+12
Volary	1E+12	1E+12	1E+12	1E+12	27	0	51	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	19	1E+12	1E+12
ČK	1E+12	1E+12	1E+12	1E+12	1E+12	51	0	33	1E+12	1E+12	1E+12	1E+12	1E+12	39	38	26
Trhové Sviny	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	33	0	24	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	22
Třeboň	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	24	0	28	34	1E+12	1E+12	1E+12	1E+12	27
JH	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	28	0	28	1E+12	1E+12	1E+12	1E+12	1E+12
Soběslav	20	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	34	28	0	27	1E+12	1E+12	1E+12	41
Týn nad Vltavou	32	28	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	27	0	22	1E+12	1E+12	33
Vodňany	1E+12	22	26	26	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	22	0	24	21	33
PT	1E+12	1E+12	1E+12	25	23	19	39	1E+12	1E+12	1E+12	1E+12	1E+12	24	0	19	1E+12
Netolice	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	38	1E+12	1E+12	1E+12	1E+12	1E+12	21	19	0	26
ČB	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	26	22	27	1E+12	41	33	33	1E+12	26	0

Fig. 3 Formation of the initial matrix C_0 of the graph direct distances (source: Authors)

The symbol p(h) represents the direct distance between nodes v_i and v_j . Thus, if there is an edge in the graph directly connecting node v_i with node v_j , then we record to the matrix of direct distances the edge evaluation $\varphi(h)$ (= distance) between these nodes [7].

If the direct distance between nodes v_i and v_j does not exist, we write to the matrix of direct distances the symbol ∞ (in our case in Fig. 3, the symbol ∞ represents the large number 10^{12}).

2) The sequence of matrices C_k , where k = 1, ..., n is being gradually constructed. In this cycle, for k = 1, ..., n, we search whether the way from the vertex v_i to v_j cannot be shortened through the vertex v_k (see the schematic representation in Fig. 4) [8].

For all $i, j \neq k$ we recalculate the elements in the matrix C_k according to the relation [9]:

$$c_{ij}^{(k)} = \min\{c_{ij}^{(k-1)}, c_{ik}^{(k-1)} + c_{kj}^{(k-1)}\}, \text{ where } i, j, k = l, ..., n.$$
 (2)

Thus for the matrix C_1 (see in Fig. 5), its elements are as follows.:




Fig. 4 Schematic representation of shortening the way from the vertex v_i to v_j through the vertex v_k (source: Authors)

3) If k = n, then the final matrix C_n is the searched matrix of minimal distances of the graph; thus, for all pairs of nodes i and j applies c_{ij} = d_{ij}, where d_{ij} is the distance (= the distance of the shortest path) between the nodes v_i and v_j for all i, j = 1, ..., n. The final matrix C_n = D is called **distance matrix** [10 and 11].

The final distance matrix D for transport network model in South Bohemia is shown in Figure 6 including minimal distances

C,	TA	PI	ST	Volvně	Vimperk	Volary	CK	T. Svinv	Třehoň	JH	Soběslav	Týn n. Vlt.	Vodňany	PT	Netolice	CB
TA	0	45	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	20	32	1E+12	1E+12	1E+12	1E+12
PI	45	0	22	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12		65	28	22	1E+12		1E+12
ST	1E+12	22	0	13	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	26	1E+12	1E+12	1E+12
Volyně	1E+12	1E+12	13	0	18	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	26	25	1E+12	1E+12
Vimperk	1E+12	1E+12	1E+12	18	0	27	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	23	1E+12	1E+12
Volary	1E+12	1E+12	1E+12	1E+12	27	0	51	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	19	1E+12	1E+12
CK	1E+12	1E+12	1E+12	1E+12	1E+12	51	0	33	1E+12	1E+12	1E+12	1E+12	1E+12	39	38	26
Trhové Sviny	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	33	0	24	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	22
Třeboň	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	24	0	28	34	1E+12	1E+12	1E+12	1E+12	27
JH	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	28	0	28	1E+12	1E+12	1E+12	1E+12	1E+12
Soběslav	20 (65	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	34	28	0	27	1E+12	1E+12	1E+12	41
Týn nad Vltavou	32	28	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	27	0	22	1E+12	1E+12	33
Vodňany	1E+12	22	26	26	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	22	0	24	21	33
PT	1E+12	1E+12	1E+12	25	23	19	39	1E+12	1E+12	1E+12	1E+12	1E+12	24	0	19	1E+12
Netolice	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	38	1E+12	1E+12	1E+12	1E+12	1E+12	21	19	0	26
ĊB	1E+12	1E+12	1E+12	1E+12	1E+12	1E+12	26	22	27	1E+12	41	33	33	1E+12	26	0

Fig. 5 Formation of the new matrix C_1 from C_0 (the elements c_{ij} which have been changed are marked in red) (source: Authors)

C ₁₆ = D	TA	PI	ST	Volyně	Vimperk	Volary	CK	T. Sviny	Třeboň	JH	Soběslav	Týn n. Vlt.	Vodňany	PT	Netolice	CB
TA	0	45	67	80	98	97	87	78	54	48	20	32	54	78	75	61
PI	45	0	22	35	53	65	81	77	82	83	55	28	22	46	43	55
ST	67	22	0	13	31	57	77	81	86	103	75	48	26	38	47	59
Volyně	80	35	13	0	18	44	64	81	86	103	75	48	26	25	44	59
Vimperk	98	53	31	18	0	27	62	90	95	121	93	66	44	23	42	68
Volary	97	65	57	44	27	0	51	84	91	119	92	65	43	19	38	64
ČK	87	81	77	64	62	51	0	33	53	81	67	59	59	39	38	26
Trhové Sviny	78	77	81	81	90	84	33	0	24	52	58	55	55	67	48	22
Třeboň	54	82	86	86	95	91	53	24	0	28	34	60	60	72	53	27
JH	48	83	103	103	121	119	81	52	28	0	28	55	77	100	81	55
Soběslav	20	55	75	75	93	92	67	58	34	28	0	27	49	73	67	41
Týn nad Vltavou	32	28	48	48	66	65	59	55	60	55	27	0	22	46	43	33
Vodňany	54	22	26	26	44	43	59	55	60	77	49	22	0	24	21	33
PT	78	46	38	25	23	19	39	67	72	100	73	46	24	0	19	45
Netolice	75	43	47	44	42	38	38	48	53	81	67	43	21	19	0	26
ĊB	61	55	59	59	68	64	26	22	27	55	41	33	33	45	26	0

Fig. 6 The final distance matrix $C_{16} = D$ (source: Authors)

from every major city to one another along existing \boldsymbol{I} and \boldsymbol{II} class roads.

3. Conclusion

The main objective of this paper was to describe the issue of searching for optimal paths in networks as one of the key areas of graph theory. For illustration, one of the most common tasks of graph theory was described - the task of searching for minimal

path, which was, by means of using Floyd algorithm, applied to a particular transport network of the South Bohemian region [12].

The task solution is represented by the abovementioned distance matrix D indicating the minimum distances from each node of the network to another one. This procedure is applicable to other transport networks as well (road network in the Czech Republic) and has a practical use, for example in logistics (route planning, transport service of territorial units etc.) and other sectors of transport (telecommunications etc.).

References

- [1] BABULAK, E., WANG, M.: Discrete event simulation: State of the art, IJOE, vol. 4, No. 2, 2008, pp. 60-63.
- [2] KUCERA, L.: Combinatorial Algorithms (in Czech), Mathematical seminar. Praha: SNTL, 1989.
- [3] PASTOR, O., TUZAR, A.: Theory of Transport Systems (in Czech), Praha: ASPI, 2007.
- [4] BARTUSKA, L., CEJKA, J., CAHA, Z.: The Application of Mathematical Methods to the Determination of Transport Flows, *Nase More*, vol. 62, pp. 91-96, 2015.
- [5] Internet source. Map portal: http://www.mapy.cz
- [6] KUBASAKOVA, I., KAMPF, R., STOPKA, O.: Logistics Information and Communication Technology, *Communications Scientific Letters of the University of Zilina*, vol. 16, No. 2, pp. 9-13, 2014.
- [7] STOPKA, O., KAMPF, R., KOLAR, J., KUBASAKOVA, I., SAVAGE, C.: Draft Guidelines for the Allocation of Public Logistics Centres of International Importance, *Communications Scientific Letters of the University of Zilina*, vol. 16, No. 2, pp. 14-19, 2014.
- [8] SIMKOVA, I., KONECNY, V.: Key Performance Indicators in Logistics and Road Transport, *Logi Scientific J. on Transport and Logistics*, 2014, vol. 5, No. 2, pp. 87-96, ISSN 1804-3216.
- [9] MOCKOVA, D.: Fundamentals of the Theory of Transport (in Czech), Praha: Publisher CVUT, 2007.
- [10] KLAPITA, V., MAJERCAKOVA, E.: Implementation of Electronic Data Interchange (EDI) as a Modern Method of Communication between Business Partners, Logi - Scientific J. on Transport and Logistics, 2014, vol. 5, No. 1, pp. 21-39, ISSN 1804-3216.
- [11] BRUMERCIK, F., KRZYWONOS, L.: Integrated Transportation System Simulation, *Logi Scientific J. on Transport and Logistics*, 2013, vol. 4, No. 2, pp. 5-10, ISSN 1804-3216.
- [12] FUTYU, I., GAL, G.: Implementing the Qualitative Consistency of Traffic Flows in Equilibrium Models, *Logi Scientific J. on Transport and Logistics*, 2013, vol. 4, No. 1, pp. 40 52, ISSN 1804-3216.